

## SAFETY DATA SHEET (SDS)

### 1. Chemical Product and Company Identification

#### 1.1 Product name

TOYOLAC Glass Fiber Reinforced ABS//PBT Resin (TOYOLAC VX10G)

#### 1.2 Recommended use of the chemical and restrictions on use

Recommended Use : For household appliances, electronic materials and industrial materials.  
Use Restriction : TORAY MAKES NO REPRESENTATION OR WARRANTY, WHETHER EXPRESSED OR IMPLIED, IN RESPECT OF FITNESS FOR A PARTICULAR PURPOSE AND SAFETY OF THIS MATERIAL.  
YOU WILL BE SOLELY RESPONSIBLE FOR ASCERTAINING THE SUITABILITY OF THIS MATERIAL FOR YOUR PURPOSE, INCLUDING BUT NOT LIMITED TO, MEDICAL APPLICATION OR FOOD CONTACT APPLICATION PURPOSES. AND DO NOT USE FOR AN INTERNAL IMPLANTATION.

#### 1.3 Supplier's detail

Name of Supplier : Toray Plastics (Malaysia) Sdn. Bhd.  
Address : 2628 MK.1, SPT., Lorong Perusahaan 4, Prai Free Industrial Zone, 13600 Prai, Penang, Malaysia.  
Telephone No. : +60-4-3988-088  
Fax No. : +60-4-3908-975, +60-4-3977-264

Sales  
Department : Sales & Marketing Department  
Manager : General Manager

Technical  
Department : Technology Centre  
Manager : Technology Centre Manager

#### 1.4 Emergency phone number

+60-4-3988-088

---

### 2. Hazards Identification

#### 2.1 GHS classification

This product is not classified under hazardous according to JIS Z 7252: 2014 (Labeling of chemicals based on GHS).

#### 2.2 GHS label elements

Not applicable

#### 2.3 Other hazards which are not covered by GHS

This product may release small amount of volatile gases which may cause irritation to eyes, nose and throat. Use adequate local exhaust ventilation during drying and molding of the product. Sweep up and dispose any spilled product to eliminate slipping hazards. Do not pile up the product too high to avoid any injuries caused by falling of the product.

#### 2.4 Major symptom and envisioned emergency

No information available

## SAFETY DATA SHEET (SDS)

### 3. Composition / Information on Ingredients

Substance / Mixture : Mixture  
Chemical Name : Mixture of Acrylonitrile-Butadiene-Styrene Copolymers and Additives  
Synonyms : Glass Fiber Reinforced ABS//PBT Resin

	Common chemical name	Chemical formula	CAS No.	ENCS No.	ISHL No.	Composition
1	Acrylonitrile-Butadiene-Styrene Copolymer (or Mixture of A, B and / or C)	—	Regd.	Regd.	Existing	75% or more
A	Acrylonitrile-Butadiene-Styrene Copolymer	-[(C8H8)k-(C3H3N)l-(C4H6)m]n-	9003-56-9	6-176	Existing	—
B	Polybutylene-Terephthalate	-(C12H12O4)-	26062-94-2	7-1039	Existing	—
C	Acrylonitrile-Styrene Copolymer	-[(C8H8)k-(C3H3N)l]m-	9003-54-7	6-126	Existing	—
D	Copolymer of Acrylonitrile, Styrene and other component (other component: 0-10%)	—	Regd.	Regd.	Existing	—
2	Glass Fiber	SiO2.Ai2O3.(Ca,Mg)O.B2O3.(Na,K)2O	65997-17-3	Regd.	—	20% or less
3	Additives	—	Regd.	Regd.	Existing	5% or less

### 4. First-Aid Measures

#### 4.1 Inhalation

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
In case of accident by inhalation: remove casualty to fresh air and keep at rest.  
It is not likely for the resin pellets to be inhaled. In case of inhalation of gases and fumes from melting resin, remove casualty to fresh air. If the casualty has difficulties in breathing or coughing, seek medical assistance immediately.

#### 4.2 Skin contact

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
Wash skin thoroughly with water and mild soap. In case of contact with melting resin, cool rapidly with water and seek medical assistance immediately. In case of contact with fume condensate from melting resin, wash thoroughly the affected area with water and soap. Seek medical assistance immediately if irritation develops.

#### 4.3 Eye contact

Gently rinse the affected eyes with clean water for at least 15 minutes. If the casualty wears contact lenses, have them removed and continue rinsing. Avoid the casualty from rubbing eyes. Transport casualty to the nearest medical facilities for treatment as soon as possible.

#### 4.4 Ingestion

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

#### 4.5 Most Important Symptoms/effects, both acute and delayed

No information available

#### 4.6 Indication of immediate medical attention and special treatment needed

No information available

#### 4.7 Protective measures for a first-aid person

Wear protective gloves when removing melting polymer or high temperature polymer.

## SAFETY DATA SHEET (SDS)

### 5. Fire-Fighting Measures

#### 5.1 Extinguishing media

In case of fire, use water mist, water jet, foam, dry powder or carbon dioxide.

#### 5.2 Specific hazards arising from chemical

In case of fire and / or explosion, do not breathe in fumes.

Toxic gases such as carbon monoxide, carbon dioxide, nitrogen oxides will form upon combustion of this product. Fires involving this material may produce large amounts of sooty smoke.

#### 5.3 Specific fire-fighting measures

Apply water from a safe distance to cool and protect surrounding area. Move container from fire areas if it can be done without risk. Keep personnel removed from and upwind of fire. Evacuate non-essential personnel to safe area.

#### 5.4 Special protective action fire fighters

Fire fighters should wear proper protective equipment.

---

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Sweep up spilled resin pellets on road or floor to avoid slipping.

#### 6.2 Environmental precautions

Do not flush into sewer or drain.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up, place in bag and hold for waste disposal.

#### 6.4 Preventive measures for secondary accident

Shut off all sources of ignition. No flares, smoking or flames in area.

---

### 7. Handling and Storage

#### 7.1 Handling

Exposure control for handling personnel:

When using do not eat or drink.  
When using do not smoke.  
Do not breathe dust.  
Do not breathe gas / fumes.

Protective measures against fire & explosion:

Take precautionary measures against static charges.

Local ventilation / total air ventilation:

Use adequate local ventilation to remove fumes generated from molten resin during processing with molding machine or extruder. Use total ventilation with ventilation fans if above work are carried out in a building.

Safety measures / incompatibility:

Do not empty into drains.

## SAFETY DATA SHEET (SDS)

Avoid rough handling or dropping. Do not breathe the fumes generated during processing of the resin, because it stimulates skin and respiratory organs. Prevent deposition of dust, because a dust explosion may happen with the presence of static electricity or electric spark.

### 7.2 Storage

Recommendation for storage:

This product is a flammable material. Follow fire defense law and local regulations for storage and handling. Keep the product away from direct sunlight, water leak, moisture and any source of heat and ignition. Store it in a well-ventilated and locked up place.

Incompatible storage condition:

Keep away from heat.

Recommendation on container and packaging materials:

Use unbreakable containers and packaging materials that satisfy the storage condition.

---

## 8. Exposure Control / Personal Protection

### 8.1 Control parameters

Administrative levels (Industrial Safety and Health Act)  
Administrative levels are not established.

Japan Society for Occupational Health and ACGIH do not determine the adopted value of powder-dust. Generally, data shown below is known about dusts.

Recommended value of Japan Society for Occupational Health (2008) – Class 3 dust:  
The weighted average per hour: inhaled dusts 2 mg/m<sup>3</sup>, total dusts 8 mg/m<sup>3</sup>

Recommended value of ACGIH (2003) – General dust:  
The weighted average per hour: inhaled dust 3 mg/m<sup>3</sup>, total dusts 10 mg/m<sup>3</sup>

DNEL(Derived No Effect Level)  
No information available.

PNEC(Predicted No Effect Concentration)  
No information available.

Glass fiber

Japan Society for Occupational Health (2008) : 2 mg/m<sup>3</sup>

### 8.2 Exposure control

Use adequate local ventilation to remove fumes generated during processing of the resin and to maintain comfortable work environment.

### 8.3 Individual protection measures

Respiratory protection:

Wear dust protective mask to avoid from inhaling dust generated during machining, sanding and etc. Wear respirator for organic gases to avoid from inhaling fumes generated during processing of the resin.

Hand protection:

It is desirable to wear protection gloves to avoid direct contact of skin with the resin. Wear heat resistant protection gloves during handling of melting polymer or high temperature polymer.

Eye protection:

Wear protective eye glasses with side shields or chemical safety goggles.

## SAFETY DATA SHEET (SDS)

Skin and body protection:

It is desirable to wear long sleeve clothing so as not to touch skin directly. Wear protection clothing of heat-resistance when handling melting polymer.

---

### 9. Physical and Chemical Properties

Appearance	: Pellet shaped solid
Color	: Light yellow
Odor	: None
Odor threshold	: No information available
pH	: N/A
Melting point	: This product softens gradually over a broad temperature range (130–150°C)
Boiling point	: No information available
Boiling range (Mixture)	: No information available
Flash point	: No information available
Evaporation rate	: No information available
Flammability (solid, gas)	: No information available
Explosion limit (Upper)	: No information available
Explosion limit (Lower)	: 60g/m <sup>3</sup> (particle size < 0.2mm)
Vapor pressure	: No information available
Vapor density	: No information available
Relative density	: 1.25 - 1.31
Solubility	: Insoluble in water. Partly soluble in organic solvent.
Octanol / water partition coefficient	: No information available
Auto-ignition temperature	: About 405°C
Decomposition temperature	: No information available
Viscosity	: No information available

---

### 10. Stability and Reactivity

#### 10.1 Reactivity

Nothing particular

#### 10.2 Chemical stability

This product is considered a stable material under normal and anticipated storage and handling conditions.

#### 10.3 Possibility of hazardous reactions

This product is considered a stable material under normal and anticipated storage and handling conditions.

#### 10.4 Conditions to avoid

Direct sunlight, fire, sources of heat etc.

#### 10.5 Incompatible materials

None

#### 10.5 Hazardous decomposition products

Black smoke, carbon monoxide, carbon dioxide, nitrogen oxides and etc maybe generated in the case combustion of this product.

---

## SAFETY DATA SHEET (SDS)

### 11. Toxicological Information

Acute toxicity	: Not classified
Skin corrosion / irritation	: Classification not possible. (N/A)
Serious eye damage / eye irritation	: Classification not possible. (N/A)
Respiratory or skin sensitization	: Classification not possible. (N/A)
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ / systemic toxicity (Single exposure)	: Not classified
Specific target organ / systemic toxicity (Repeated exposure)	: Not classified
Aspiration hazards	: Classification not possible. (N/A)
Other hazard(s)	: No information available

This product is classified into the above classifications based on judgment theory of a mixture.

### 12. Ecological Information

Ecological toxicity (Acute)	: Not classified
Ecological toxicity (Chronic)	: Not classified
Persistence & biodegradability	: Classification not possible. (N/A)
Bioaccumulation potential	: Classification not possible. (N/A)
Mobility in soil	: Classification not possible. (N/A)
Adverse effect to the ozone layer	: Classification not possible. (N/A)
Other adverse effects	: No information available

This product is classified into the above classifications based on judgment theory of a mixture.

### 13. Disposal Consideration

Dump the waste matters following law, rules and regulations.  
Dispose to an authorized waste collection point.  
Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.  
Check if there is no resin left, if disposing the package after use. (paper package, flexible container etc.)  
Do not use the package for other purposes.

### 14. Transport Information

UN number	: Not applicable
UN proper shipping name	: Not applicable
Transport hazard class(es)	: Not applicable
Packing group	: Not applicable
Environmental hazards	: Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: Not applicable
The Laws and Regulations for transportation in Japan	: Not applicable
ERG Guide No.	: Not applicable

Special precautions for user  
No information available

Specific safety measures and conditions on transport:

Avoid wetting or rough handling so that the packaging will not be damaged. In case the bags are damaged and the pellets are scattered, pay attention so that no one will slip and fall. All of the spilled product should be collected immediately and placed in proper labeled container for dispose or recovery. Take precautionary measures against static discharges when using pneumatic transportation.

## SAFETY DATA SHEET (SDS)

### 15. Regulatory Information

Other regulatory information:

We are not able to check up the regulatory information in regard to the substances in your country or region. Therefore, we request this matter would be filled by your responsibility. Regulatory information with regard to this product in your country or in your region should be examined by your own responsibility. Ensure this product in compliance with federal requirements and ensure conformity to local regulations.

---

### 16. Other Information / References

Date of issue            10/06/2019  
Revised items            Revision according to contents of the revised SDS from Toray Japan (JIS Z 7253:2012)

Disclaimer:

The information relates to this specific material. It may not be valid for this material, if used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his own particular use.

The information herein is given in good faith, but no warranty, express or implied, is made. Please consult us for further information.

To the best of our knowledge, the information contained herein is accurate. However, we assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of user. All materials may present unknown hazards and should be used in caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

This information contained in this data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It is advised to make their own tests to determine the safety and suitability of each such product or combination for their own purposes.